

10 YEAR WARRANTY



colorpan-Cladding Profiles are renowned for their:

- high impact resistance and breaking strength
- consistent compression-moulded surface structure
- coating which offers optimum light fastness (DIN 54 004 Level 8)
- wood preservation in accordance with DIN 68 800 Part 5
- structural perfection in respect of non-bearing curtain wall cladding functionality.

Warranty stipulation: This product must be installed strictly in accordance with our instructions.

In addition to the guarantee from your supplier, Werzalit offers the following warranty for a period of 10 years from the date of the sales invoice:

Should a defect arise in one of our products within the specified period which prevents the product from being used for the intended purpose, we guarantee to take one of the following courses of action of our own choice: replace the item, undertake a repair or reimburse you with the purchase price appropriately.

(Repair work does not include the removal and refitting of profiles.)

This guarantee assumes that the product we have supplied is properly installed according to Werzalit's instructions and subject to proper use. Damage caused by external factors or force majeure is not covered by this warranty.

Any claim under this additional warranty must be received by Werzalit in writing within 10 years of the invoice date or of the date of the written sales contract, where no invoice was issued.

WERZALIT.

Safety and quality – signed, sealed and delivered.

werzalit®
LASTING. BEAUTY.

10 YEAR WARRANTY



This Werzalit warranty applies to the item/delivery specified below and is only valid on presentation of the invoice and/or the sales contract.

Designation of item	
Name of purchaser	
Address of purchaser	
Invoice date	
Date of installation	

Colorpan Cladding Profiles are manufactured with the utmost care using specially selected materials. The manufacturing process and the raw materials used are founded on 35 years of experience in the production and application of Werzalit components for outdoor use.

Colorpan Cladding Profiles consist essentially and exclusively of healthy thinning material harvested from native woodland. They are hardened with high grade duroplastic resins and impregnated with a fungicide.

The colour surface consists of a high grade coating with especially light-resistant pigments, qualities which have given outstanding performance in outdoor applications for decades. We use water-soluble coated systems exclusively. No solvents are used whatsoever.

The high temperature controlled drying process of our acrylic paint system enhances its physical properties still further to achieve a high degree of scratch and abrasion resistance. The coating's special material properties provide outstanding weather-resistance and excellent embrittlement resistance, even when subjected to intense UV radiation and extreme weather conditions. Complies fully with DIN 54 004 Level 8 light fastness requirements.

Stuttgart will be the exclusive place of jurisdiction in all warranty claims brought by merchants.

Oberstenfeld, April 2005

WERZALIT.

Safety and quality – signed, sealed and delivered.

werzalit®
LASTING. BEAUTY.